

PRO VISION

Page: 1

Compilation date: 07/03/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRO VISION

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Proficio Limited

52 Crossgates

Bellshill

Lanarkshire

ML4 2EE

Scotland

Tel: 01698740840

Fax: 01698740008

Email: sales@proficio.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

PRO VISION

Page: 2

1-10%

skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	30-50%		
1-METHOXY-2-PROPANOL						

Section 4: First aid measures

203-539-1

4.1. Description of first aid measures

107-98-2

Skin contact: Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if any discomfort continues.

Eye contact: Immediately flush with plenty o fwater for up to 15 minutes. Remove any contact lenses and open

eyes wide apart. Get medical attention immediately. Continue to rinse with water.

Ingestion: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. If

Flam. Liq. 3: H226; STOT SE 3: H336

vomiting occurs, the head should be kept low. Get medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Get medical attention

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Repeated exposure may cause skin dryness or cracking.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat if inhaled directly in confined/poorly ventilated space. Vapours

may cause dizziness and drowsiness

${\bf 4.3.}\ Indication\ of\ any\ immediate\ medical\ attention\ and\ special\ treatment\ needed$

Section 5: Fire-fighting measures

PRO VISION

Page: 3

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder. Water fog.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Flammable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and

eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or water courses or onto the ground. Spillages or uncontrolled discharges

into water courses must be reported to SEPA/EPA immediately.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water. Transfer to a

closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Use non-sparking tools. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly

closed.

7.3. Specific end use(s)

Specific end use(s): PC35: Washing and cleaning products (including solvent based products).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PRO VISION

Page: 4

PROPAN-2-OL

Workplace exposure limits:

Respirable dust

	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
Ī	UK	999 mg/m3	1250 mg/m3	-	-

1-METHOXY-2-PROPANOL

UK	375 mg/m3	560 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in section

7 of SDS are in place.

Respiratory protection: If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149

Hand protection: Chemically protective gloves according to DIN EN 374 with CE labelling

Eye protection: Eye and face protection to comply with European Standard EN166

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place. Prevent from entering in

public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Green

Solubility in water: Highly soluble

Odour: Characteristic odour

indiana in indiana

Viscosity: Non-viscous

Boiling point/range°C: >90 Flash point°C: 23 - 60

Relative density: 0.91 pH: 7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: The following materials may react with the product: strong oxidising agents; strong acids.

10.2. Chemical stability

Chemical stability: Stable at normal ambient temperatures and when used as recommended

PRO VISION

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Solvent vapours may form explosive mixtures with air

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Alkali metals. Amines.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Hazardous ingredients:

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Repeated exposure may cause skin dryness or cracking.

Eye contact: There may be irritation and redness.

PRO VISION

Page: 6

Ingestion: Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat if inhaled directly in confined/poorly ventilated space. Vapours

may cause dizziness and drowsiness

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

 $\textbf{NB:} \ \ \text{The user's attention is drawn to the possible existence of regional or national regulations regarding}$

disposal

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 3

PRO VISION

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be

used only as a guide. This company shall not be held liable for any damage resulting from handling or

from contact with the above product.